



The Wireless Area Radiation Monitor (WAM) 500 P (Portable) is a hand-held, wireless, gamma radiation monitor.

Key Features

- •Integrated Internal GM detector
- •External GM detector (optional); 250' max length
- Large, bright LCD display
- Intuitive membrane key panel
- Integrated wireless
- •NEMA Rated Enclosure

Benefits

- ✓Tremendous Value (benefit/cost)
- √Flexible Wireless Communication design: easily integrates into existing platforms
- ✓ Dual Function: Portable Survey Meter and/or temporary dose rate area monitor

Applications

- Use as personal dose rate meter
- Connect to external detector for wireless, remote monitoring of Rad Waste, RX Cavity or Cubicle dose rates
- Spent Fuel Pool, Underwater, diving activites
- Drill/training E Plan scenario; can wirelessly write simulated dose rates to unit— Authentic update



Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net



WAM-500 P

- Dimensions: 6" (I) x 3" (high) x 1" (d))
- Temperature: -40°F -170° F
- Operate in 10-95% RH environment
- Rugged case; Industrial and Splash proof (IP 55 rating))
- Electrical: 110 VAC with supplied adapter, USB powered, or 9-30 VDC
- Network Connection: Ethernet Connection: *Coming Soon
- External I/O Connections
- Wireless Communications: Optional 'MESH' Radio, or standard 900 MHz
 or 2.4 GHz; standard WIFI connectivity available

Radiation Detection:

- Gamma Detection
- Energy Compensated GM Detector (LND GM Detector)

Multi -Ranges available:

- 0.3 mrem/h 9 R/h
- 1mrem/h 90 R/h
- 10mrem/h 900 R/ h

*Use Stand Alone or With IIS ALARACAST or Equivalent Remote Monitoring Software Systems (Note: System must have compatibility with specific wireless option selected or with Ethernet (network) protocol; IIS can work with customer to optimize communication)

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net