

Innovative Industrial Solutions



I.I.S.

WAM Trainer



WAM-P Training Unit



WAM-D Training Unit

The WAM Trainer System utilizes IIS's WAM 500 series to provide real-time, authentic *SIMULATED* radiation levels in a hand-held or area monitor training instrument.

- Standalone functionality; (pre-loaded list of 100 scenario points) for quick, easy training deployment
- Scenario Functionality; True time sequenced, wirelessly transmitted data from data tables; receive chronological time/date stamped data. *Requires IIS Base Radio to be configured to WAM Trainer PC.
- Multiple WAM's can be included in wireless scenario mode
- Stat/Stop/Pause allows for taking 'time out' during training scenario for instruction/break, etc.

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net

Innovative Industrial Solutions



I.I.S.

WAM Trainer

Additional Features:

- Available on WAM D and WAM P models
- Clearly identified WAM Training Status; Units have bright yellow labeling
- Easy configuration via WAM Pro Software (WAM Training functionality sold as upgrade) to standard WAM Pro system
- IIS Radio Base Station (additional component) required for WAM Trainer Scenario option; (maybe put a picture of unit on back!

**All WAM Training Units are sold WITHOUT Standard GM Radiation Detectors unless otherwise noted*



Wireless Options:

- 900 MHz
- 2.4 GHz Wi-fi (802.11)
- 2.4 GHz Zigbee

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net

Innovative Industrial Solutions



I.I.S.

WAM Trainer



WAM-P Training Unit

- Dimensions: 6" (l) x 3" (wide) x 1" (d))
- Temperature: 12-150° F
- Operate in 10-95% RH environment
- Rugged case; Industrial and Splash proof (IP 55 rating) ; gasket sealed
- Electrical : 110 V AC or Battery Powered
- Network Connection: Ethernet Connection
- External I/O Connections (optional)



WAM-D Training Unit

- Dimensions: 6.25" (l) x 3.5" (high) x 2.5" (d))
- Temperature: 12-150° F
- Operate in 10-95% RH environment
- Rugged case; Industrial and Splash proof (IP 55 rating))
- Electrical : 110 V AC or Battery Powered
- Network Connection: Ethernet Connection
- External I/O Connections (optional)

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net

Innovative Industrial Solutions



I.I.S.

WAM Trainer

Time	WAM:1234			WAM:5678		
	Int. Rate (mrem/h)	Ext. Rate (mrem/h)	Variance (%)	Int. Rate (mrem/h)	Ext. Rate (mrem/h)	Variance (%)
10:55:00	10	0	10	100	0	10
10:55:20	250	0	10	400	0	10
10:55:40	750	0	10	750	0	10
10:56:00	1200	0	10	1500	0	10
10:56:20	2000	0	10	3000	0	10
10:56:40	3000	0	10	5000	0	10
10:57:00	5000	0	10	6000	0	10

WAM Scenario Training Software Screen

Set times of dose changes, loops, Int. Rate, Ext. Rate, Variance % that give a variety of scenarios in your training exercises to put your trainees through.

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net