## Rechargeable WAM



- Battery Run Time:14 Days
- 120 Amp Hour rechargeable battery
- Includes 3A charges

- NEMA Rated Enclosure
- Splash Proof/Dust Proof
- Clear Window for viewing
- 8.6" L x 6.6" W x 5.5" H Weighs 7.5 lbs.
- Convenient carry handle
- Includes a mag mount

Innovative Industrial Solutions, Inc.

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net

## Rechargeable WAM

- Dimensions: 8.6" L x 6.6" W x 5.5" H Weighs 7.5 lbs.
- Temperature: -12°F -150° F
- Operate in 10-95% RH environment
- Rugged case; Industrial and Splash proof (IP 55 rating)
- Wireless Communications: Optional 'MESH' Radio, or standard 900 MHz or 2.4 GHz; standard WIFI connectivity available

## **Radiation Detection:**

Gamma Detection

**Energy Compensated GM Detector** 

(LND GM Detector)

## Multi -Ranges available:

0.3 mrem/h - 9 R/h

1mrem/h - 90 R /h

10mrem/h - 900 R/h

\*Use Stand Alone or With IIS ALARACAST or Equivalent Remote Monitoring Software Systems (Note: System must have compatibility with specific wireless option selected; IIS can work with customer to optimize communication)

**Innovative Industrial Solutions, Inc.** 

2830 Skyline Drive Russellville, AR 72802

Phone (479) 968-4266

Fax (479) 890-9072

www.i-i-s.net